


TL 250  
TL 350  
TL 450



**Technology at a Glance**

- Precise and safe work by cutting from below
- Fast setting for mitre cuts
- Workpiece stop can be moved to extend cutting area
- Saw blade guard, electrical overload protection and no-voltage release
- Workpiece clamping with adjustable clamping device and hardwood clamping block for tightening on both sides of the saw blade



**Cutting Area**

- TL 250, TL 350, TL 450



**Transportable Saws**

- Trouble-free operation on construction sites

Technical Data		TL 250	TL 350	TL 450
Sawblade	Ø mm	250	350	450
Drive performance	kW	1,1	2,0	2,2
Cutting speed	m/min	2700	3200	4100
Machine dimension (L X W X H)	mm	45x67x68	45x84x75	61x107x144
Machine Weight	kg	56	68	
Working range	mm	75	110	145
Working range Square	mm	65x65	100	130
Working range Roundmaterial	mm	75	110	145
Mitre range		30/90/30	30/90/30	30/90/30
Tools		Carbide Tools	Carbide Tools	Carbide Tools

Circular Sawing Machines  
Band Sawing Machines  
Drilling Machines  
Coping/Welding Robots  
Plateprocessing Centers  
Punch-/Shear Machines  
Shotblast Systems  
Painting Systems  
Automation  
Service