PEMA SPSi 1500

Skyhook PRO series - Making things easy.



PROGRAMMABLE – DIGITAL – VISUAL

PEMA SPSi Skyhook PRO positioners are build for demanding tasks with heavy work-pieces with even the most complex product geometry. With a Skyhook PRO, work-pieces are easily set up in a wide variety of attitudes. Loading capacity range is 750-15 000 kg.

- Optimal and repeatable position for ergonomics, capacity increase and simulated movements for safety. As a result welding productivity can be raised significantly compared to conventional positioner.

- PRO features are available with mobile, tablet and laptop via WiFi. PRO application runs on internet browser and includes e.g. programming for the positioner, machine diagnostic, maintenance book and possibility to add notes.

- Hundreds of man-hours saved yearly compared to manual work-piece handling. With PEMA Skyhook PRO these hours can be used on actual productive work.

MORE PRODUCTIVITY

Save all positions, lifting, rotation and tilting and modify later if needed. Skyhook PRO guarantees optimal working position, always.

Max. load (kg)	1500
Rotation speed (rpm)	0,07-1,3
Max. rotational torque (Nm)	1000
Max. tilting torque (Nm)	3000
Tilting speed (rpm)	0,1-1
Lifting time (s)	65
Tilting axle height min-max	850-1650
Offset distance (mm)	400
Max. workpiece rotation diameter (mm)	2400
Table plate diameter (mm)	700
T-slots on table plate	3x M12 DIN508
Integrated grounding, max. current (A)	700
Width (mm)	1160
Length (mm)	2980
Height (mm)	2500
Weight (kg)	2260
Main supply cable length (m)	12
Main supply connection 50 Hz	3x400VAC+(N)+PE
Power (A)	20

IMPROVED QUALITY

Good ergonomics and safety secure welder's high motivation and working quality.

DESIGNED TO LAST

Skyhook PRO positioners are engineered to endure even the most robust conditions. Partner that will not let you down.




Due to continuous R&D, Pemamek Ltd reserves the right to change the specification without notice

- Always correct welding and assembly positions
- Visual application for programming
- Durable remote control included
- Improved welding quality
- Excellent working ergonomics
- Fast production start-up
- Integration to other PEMA solutions
- High-quality components
- Extensive world-wide PEMA service



MAIN MEASUREMENTS




1043

Tilting Torque SPSi 1500

LOAD CAPACITY DIAGRAMS

Rotation torque SPSi 1500



OPTIONS

- Tablet for PRO application
- Foot pedal for PRO features and start/stop of rotation in manual mode
- Foot pedal for PRO features and speed control of rotation in manual mode
 - External control of rotation
 - Wireless remote control

